# 3.0V 3000F ULTRACAPACITOR CELL

# Maxwell's High Power and Energy Cell

Maxwell Technologies' 3.0V 3000F ultracapacitor cell is designed to support the latest trends in renewable energy, industrial electrification, and transportation. Designed from the ground up, Maxwell developed the 3.0V 3000F cell to be one of the highest energy, highest power workhorses of its ultracapacitor portfolio. Whether used alone, integrated into a module assembly, or in a hybrid configuration, Maxwell's 3.0V 3000F product will help reduce the overall cost and weight of the system while improving the customer's return on investment.

Ultracapacitors are the technology of choice for long life and high power applications because of their long operating lifetime, low maintenance requirements, and superior cold weather performance compared to batteries.

## FEATURES AND BENEFITS

- Rated at 3.0V, 3000F
- · High power & energy cell with ultra low ESR
- Improved overall performance to previous generation of 3.0V products
- DuraBlue™ Shock and Vibration Technology
- 1,500 hour DC life at maximum operating temperature and voltage\*
- Designed for up to 1,000,000 duty cycles\*
- · Laser weldable or screw post terminals
- Compliant with UL, RoHS, and REACH requirements

## **TYPICAL APPLICATIONS**

- Heavy transportation
  - Hybrid buses
  - Rail
  - Truck
  - Construction vehicles
- Heavy industrial and stationary solutions
  - Backup and UPS systems
  - STATCOM systems
- · Grid, microgrid, and microturbines
- Automotive – VSS


- EPAB

- Liftgate & Plow
- EPAS Backup power
  - X-by-wire

## **ORDERING INFORMATION**

Model Number	Part Number	Package Quantity
BCAP3000 P300 K04/05	135961 / 135962	15

\* Typical results may vary. Additional terms and conditions, including the limited warranty, apply at the time of purchase. See the warranty details for applicable operating use and requirements.



DATASHEET



# Advanced Strack & Lincaled Technology

# **PRODUCT SPECIFICATIONS & CHARACTERISTICS**

Values are referenced at  $T_A =$  room temperature and  $V_R = 3.0V$  rated voltage (unless otherwise noted). Min and Max values indicate product specifications. Typical results will vary and are provided for reference only. Additional terms and conditions, including the limited warranty, apply at the time of purchase. See the warranty details for applicable operating and use requirements.

Symbol	Parameter	Conditions	Min	Typical	Мах	Unit			
ELECTRICAL									
V <sub>R</sub>	Rated Voltage		-	-	3.0	V			
V <sub>SURGE</sub>	Surge Voltage	Note 1	_	-	3.1	V			
C <sub>R</sub>	Rated Capacitance	BOL, Note 2,8	3,000	3,140	3,600	F			
R <sub>s</sub>	Equivalent Series Resistance (ESR <sub>DC</sub> )	BOL, Note 2,8	_	0.13	0.23	mΩ			
Ι <sub>leak</sub>	Leakage Current	Note 3	-	8	12	mA			
<b>І</b> <sub>РЕАК</sub>	Peak Current	BOL, Note 4,8	-	_	2,600	А			
I <sub>MAX</sub>	Continuous Current	BOL, Note 7,8 - ∆T = 15°C - ∆T = 40°C	-		170 280	A <sub>rms</sub>			
LIFE									
t <sub>65C</sub>	High Temperature Life	$V_R = 3.0V$ and $T_A = 65$ °C, EOL, Note 8 - Capacitance change ΔC from min $C_R$ - Resistance change ΔR from max $R_S$	- - -	1,500 -20 +100	- - -	hours % %			
t <sub>25C</sub>	Projected Life Time	$V_R$ = 3.0V and T_A = 25°C, EOL, Note 8 - Capacitance change ΔC from minC <sub>R</sub> - Resistance change ΔR from maxR <sub>s</sub>	- - -	10 -20 +100	_ _ _	years % %			
n <sub>cycle</sub>	Projected Cycle Life	$T_A = 25$ °C, EOL, Note 6,8 - Capacitance change ΔC from minC <sub>R</sub> - Resistance change ΔR from maxR <sub>s</sub>	- - -	1,000,000 -20 +100		cycles % %			
t <sub>shelf</sub>	Shelf Life	Stored uncharged, $T_A \le 25^{\circ}C$ and RH $\le 50\%$ - Capacitance $\ge$ min. BOL $C_R$ - Resistance $\le$ max. BOL $R_S$	_	4	_	years			



# **PRODUCT SPECIFICATIONS & CHARACTERISTICS**

Values are referenced at  $T_A =$  room temperature and  $V_R = 3.0V$  rated voltage (unless otherwise noted). Min and Max values indicate product specifications. Typical results will vary and are provided for reference only. Additional terms and conditions, including the limited warranty, apply at the time of purchase. See the warranty details for applicable operating and use requirements.

Symbol	Parameter	Conditions	Min	Typical	Max	Unit		
POWER & ENERGY								
P <sub>d</sub>	Usable Specific Power	BOL, Note 5,8	10.2	18.1	_	kW/kg		
P <sub>MAX</sub>	Impedance Match Specific Power	BOL, Note 5,8	21.3	37.6	_	kW/kg		
E <sub>d</sub>	Gravimetric Specific Energy	BOL, Note 5,8	8.2	8.5	-	Wh/kg		
E	Stored Energy	BOL, Note 5,8,9	3.8	3.9	-	Wh		
TEMPERATURE & THERMAL								
T <sub>A</sub>	Operating Temperature	Cell case temperature	-40	25	65	°C		
T <sub>STG</sub>	Storage Temperature	Stored uncharged @ RH <u>&lt;</u> 50%	-40	-	70	°C		
R <sub>th</sub>	Thermal Resistance	Case to ambient, Note 7	_	2.3	_	°C/W		
$C_{th}$	Thermal Capacitance		-	430	_	J/°C		
PHYSICAL								
m	Mass		_	460	_	g		
_	Recommended Torque on Threaded connector (K04)	M12 Thread	10	12	14	Nm		
_	Recommended Welding on Jove Terminal (K05)	Negative: 1100-F aluminum Positive: 1070-F aluminum Refer to Maxwell K2 Cell Family Welding Guidelines (maxwell.com)	_	_	_	_		
_	Vibration		ISO <sup>-</sup>	-				
_	Shock		I	_				
SAFETY								
_	Certifications		UL81					



# NOTES

#### 1. Surge Voltage

> Absolute maximum voltage, non-repetitive. Duration not to exceed 1 second.

#### 2. Rated Capacitance and ESR<sub>DC</sub>

> Measured at 25°C per document number 1013823 available at www.maxwell.com.

#### 3. Leakage Current

- $\,>\,$  Current measured after 72 hours of constant voltage hold at V\_R and 25°C. Initial leakage current can be higher.
- If applicable, module leakage current is the sum of cell leakage current and bypass current created by balancing circuit.

#### 4. Peak Current

> Current needed to discharge cell or module from  $V_R$  to  $1/2V_R$  in 1 second.

$$I_{\text{PEAK}} = \frac{\frac{1}{2}V_{\text{R}}}{\frac{1}{2}V_{\text{R}}}$$

where I<sub>PEAK</sub> is the maximum peak current (A);

- $V_{\rm R}$  is the rated voltage (V);
- $\triangle$  t is the discharge time (sec);  $\triangle$  t = 1 sec in this case;
  - $C_{R}\xspace$  is the rated BOL capacitance (F);
  - $R_S$  is the maximum BOL ESR\_DC (0).
- > The stated peak current should not be used in normal operation and is only provided as a reference value.

#### 5. Energy & Power (Based on IEC 62576)

- > Usable Specific Power,  $P_d(W/kg) = \frac{0.12V_R^2}{R_S \times m}$
- > Impedance Match Specific Power,  $P_{MAX}$  (W/kg) =  $\frac{0.25V_R^2}{R_S \times m}$
- > Gravimetric Specific Energy,  $E_d$  (Wh/kg) =  $\frac{E_{MAX}}{m}$
- > Maximum Stored Energy,  $E_{MAX}$  (Wh) =  $\frac{\frac{1}{2}C_R \times V_R^2}{2500}$

 $\begin{array}{ll} \mbox{where} & V_{R} \mbox{ is the rated voltage (V);} \\ R_{S} \mbox{ is the BOL ESR}_{DC} (\Omega); \\ m \mbox{ is the typical mass (kg);} \\ C_{R} \mbox{ is the BOL capacitance (F).} \end{array}$ 

#### 6. Projected Cycle Life

- > Constant current charge-discharge cycle from  $V_R$  to  $1/2V_R$  at 25°C.
- > Cycle life is dependent upon application-specific characteristics. Actual results will vary.

#### 7. Continuous Current & Thermal Resistance

> Maximum current which can be used continuously within the allowed temperature range.

$$I_{MAX} = \sqrt{\frac{\Delta T}{R_{th} \times R_{s}}}$$

#### 8. BOL & EOL Conditions

- > BOL (Beginning of Life): Rated/Initial product performance
- > EOL (End of Life)
  - Capacitance: 80% of min. BOL rating (0.8 x min. C<sub>R</sub>)
  - ESR<sub>DC</sub>: 200% of max. BOL rating (2 x max. R<sub>s</sub>)

#### 9. Transportation Regulation Regarding Stored Energy

> Per United Nations material classification UN3499, all Maxwell ultracapacitor cells have less than 10Wh stored energy to meet the requirements of Special Provisions 361. Both individual ultracapacitors and modules composed of ultracapacitors shipped by Maxwell can be transported without being treated as dangerous goods (hazardous materials) under transportation regulations.

# **DETAILED PRODUCT DESCRIPTION**

#### Introduction

The BCAP3000 P300 K04/K05 energy storage cell is a high power and energy design in the Maxwell driven industry-standard 60mm cylindrical form factor. The 3.0V 3000F cell design uses Maxwell's proprietary DuraBlue<sup>®</sup> Advanced technology to provide maximum level of resistance against shock and vibration.


#### **Technology Overview**

Ultracapacitor, also known as supercapacitor or electric double layer capacitor (EDLC), delivers energy at relatively high rates (beyond those accessible with batteries). Ultracapacitors store charge electrostatically (non-Faradaic) by reversible adsorption of the electrolyte onto electrochemically stable high surface area carbon electrodes. Charge separation occurs on polarization at the electrolyte interface, producing a double layer. This mechanism is highly reversible, allowing the ultracapacitor to be charged and discharged hundreds of thousands to even millions of times.

#### **Ultracapacitor Construction**

An ultracapacitor is constructed with symmetric carbon positive and negative electrodes separated by an insulating ion-permeable separator and packaged into a container filled with organic electrolyte (salt/solvent) designed to provide maximum ionic conductivity and electrode wetting. It is the combination of high surface-area activated carbon electrodes (typically > 1500m<sup>2</sup>/g) with extremely small charge separation (Angstroms) that results in high capacitance.

Ultracapacitor Energy = 1/2 CV<sup>2</sup>









# **MECHANICAL DRAWINGS**

#### BCAP3000 P300 K04



#### BCAP3000 P3000 K05



Products and related processes may be covered by one or more U.S. or international patents and pending applications. Product dimensions are for reference only unless otherwise identified. Maxwell Technologies reserves the right to make changes without further notice to any products herein. "Typical" parameters which may be provided in Maxwell Technologies datasheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Please contact Maxwell Technologies directly for any technical specifications critical to application.

UCAP Power, Inc. Global Headquarters 6155 Cornerstone Court East, Suite 210 San Diego, CA 92121 USA Tel: +1 (833) UPOWER 1 Info@ucappower.com

#### Maxwell Technologies Korea Co., Ltd. 17, Dongtangiheung-ro 681 Beon-gil, Giheung-gu, Yongin-si, Gyeonggi-do 17102 Republic of Korea Tel: +82 31 289 0700 Fax: +82 31 286 6767

MAXWELL TECHNOLOGIES, MAXWELL, MAXWELL CERTIFIED INTEGRATOR, ENABLING ENERGY'S FUTURE, DURABLUE, NESSCAP, XP, BOOSTCAP, D CELL, and their respective designs and/or logos are either trademarks or registered trademarks of UCAP POWER, Inc., and/or its affiliates, and may not be copied, imitated, or used, in whole or in part, without the prior written permission of UCAP POwer, Inc. All rights reserved. No portion of these materials may be reproduced in any form, or by any means, without prior written permission from UCAP Power, Inc.

